

Caldera 7

Silicone Heat Transfer Fluid



CALDERA®
HEAT TRANSFER FLUIDS



Heat Transfer Fluids

Caldera 7 is a premium silicone heat transfer fluid. It is formulated with an advanced additive system for superior performance and also protects against oxidation, wear, rust and corrosion. Compatible with most silicone-based fluid technology on the market, Caldera 7 can be mixed at any ratio without issue. Caldera 7 is stable up to a maximum film temperature of 366°C (691°F), making it ideal for the most intensive heat transfer applications.

Applications

- Open-bath systems
- Closed loop systems with a maximum bulk temperature of 316°C (601°F)
- Open loop systems with a maximum bulk temperature of 204°C (400°F)

Performance Advantages

- Ideal for open bath systems
- Impervious to oxidation
Ideal for systems prone to premature fluid degradation

Temperature Range



Typical Properties

Caldera 7

Minimum Temperature, °C (°F)	-53 (-63)
Maximum Film Temperature, °C (°F)	366 (691)
Maximum Bulk Temperature, Closed Systems, °C (°F)	316 (601)
Maximum Bulk Temperature, Open Systems, °C (°F)	204 (400)
Pour Point, °C (°F)	-66 (-87)
Flash Point, °C (°F)	324 (615)
Fire Point, °C (°F)	336 (637)
Autoignition Point, °C (°F)	437 (819)
Thermal Expansion Coefficient, %/°C	0.105
Thermal Conductivity @ 38°C, W/m-K	0.133
Thermal Conductivity @ 260°C, W/m-K	0.101
Heat Capacity @ 38°C, kJ/kg-K	1.714
Heat Capacity @ 260°C, kJ/kg-K	2.137
Distillation Range (ASTM D2887), 10% °C	494
Distillation Range (ASTM D2887), 90% °C	679

Fluid properties are typical results and should not serve as a sole resource for determining the correct fluid for a particular application. Please consult an Isel representative to ensure that the product is the correct choice for the application. Revised 9/2018 - M

toll-free: 1-800-503-9533
phone: 904-378-3232


email: sales@iselinc.com
web: www.calderafluids.com

Caldera 7


Silicone Heat Transfer Fluid




Density




Thermal Conductivity




Kinematic Viscosity




Heat Capacity



Dynamic Viscosity



Vapor Pressure



Fluid properties are typical results and should not serve as a sole resource for determining the correct fluid for a particular application. Please consult an Isel representative to ensure that the product is the correct choice for the application. Revised 9/2018 - M

Caldera 7

Silicone Heat Transfer Fluid



Temperature (°C)	Density (kg/m ³)	Kinematic Viscosity (Centistoke)	Dynamic Viscosity (Centipoise)	Thermal Conductivity (W/m-K)	Heat Capacity (kJ/kg-K)	Vapor Pressure (kPa)
-50	981.39	288.71	283.33	0.147	1.551	0.00
-45	980.07	244.65	239.78	0.146	1.560	0.00
-40	978.75	209.03	204.58	0.145	1.569	0.00
-35	977.42	179.95	175.89	0.145	1.578	0.00
-30	976.10	156.02	152.30	0.144	1.587	0.00
-25	974.78	136.17	132.74	0.143	1.597	0.00
-20	973.46	119.58	116.41	0.142	1.606	0.00
-15	972.14	105.62	102.68	0.142	1.615	0.00
-10	970.82	93.79	91.06	0.141	1.624	0.00
-5	969.50	83.71	81.16	0.140	1.634	0.00
0	968.17	75.07	72.68	0.139	1.643	0.00
5	966.85	67.62	65.38	0.139	1.652	0.00
10	965.53	61.17	59.06	0.138	1.662	0.00
15	964.21	55.55	53.56	0.137	1.671	0.00
20	962.89	50.63	48.75	0.136	1.680	0.00
25	961.57	46.31	44.53	0.136	1.690	0.00
30	960.24	42.50	40.81	0.135	1.699	0.00
35	958.92	39.13	37.52	0.134	1.708	0.00
40	957.60	36.13	34.60	0.133	1.718	0.00
45	956.28	33.45	31.99	0.133	1.727	0.00
50	954.96	31.06	29.66	0.132	1.736	0.00
55	953.64	28.91	27.57	0.131	1.746	0.00
60	952.32	26.97	25.68	0.130	1.755	0.00
65	950.99	25.22	23.98	0.130	1.764	0.00
70	949.67	23.63	22.45	0.129	1.774	0.00
75	948.35	22.19	21.05	0.128	1.783	0.00
80	947.03	20.88	19.78	0.127	1.793	0.00
85	945.71	19.68	18.62	0.127	1.802	0.00
90	944.39	18.59	17.55	0.126	1.811	0.00
95	943.07	17.58	16.58	0.125	1.821	0.00
100	941.74	16.66	15.69	0.124	1.830	0.00
105	940.42	15.81	14.87	0.124	1.840	0.00
110	939.10	15.02	14.11	0.123	1.849	0.00
115	937.78	14.30	13.41	0.122	1.859	0.00
120	936.46	13.63	12.76	0.121	1.868	0.00
125	935.14	13.00	12.16	0.121	1.878	0.00
130	933.81	12.42	11.60	0.120	1.887	0.00
135	932.49	11.88	11.08	0.119	1.897	0.00

Fluid properties are typical results and should not serve as a sole resource for determining the correct fluid for a particular application. Please consult an Isel representative to ensure that the product is the correct choice for the application. Revised 9/2018 - M

Caldera 7

Silicone Heat Transfer Fluid



Temperature (°C)	Density (kg/m ³)	Kinematic Viscosity (Centistoke)	Dynamic Viscosity (Centipoise)	Thermal Conductivity (W/m-K)	Heat Capacity (kJ/kg-K)	Vapor Pressure (kPa)
140	931.17	11.38	10.60	0.119	1.906	0.01
145	929.85	10.91	10.14	0.118	1.916	0.01
150	928.53	10.47	9.72	0.117	1.925	0.01
155	927.21	10.06	9.33	0.116	1.935	0.02
160	925.89	9.67	8.96	0.116	1.944	0.02
165	924.56	9.31	8.61	0.115	1.954	0.03
170	923.24	8.97	8.28	0.114	1.963	0.03
175	921.92	8.65	7.97	0.113	1.973	0.03
180	920.60	8.35	7.68	0.113	1.982	0.05
185	919.28	8.06	7.41	0.112	1.992	0.06
190	917.96	7.79	7.15	0.111	2.002	0.07
195	916.64	7.54	6.91	0.110	2.011	0.09
200	915.31	7.30	6.68	0.110	2.021	0.12
205	913.99	7.07	6.46	0.109	2.030	0.16
210	912.67	6.85	6.25	0.108	2.040	0.19
215	911.35	6.65	6.06	0.108	2.050	0.23
220	910.03	6.45	5.87	0.107	2.059	0.30
225	908.71	6.27	5.69	0.106	2.069	0.38
230	907.38	6.09	5.53	0.105	2.079	0.48
235	906.06	5.92	5.37	0.105	2.088	0.61
240	904.74	5.76	5.21	0.104	2.098	0.77
245	903.42	5.61	5.07	0.103	2.108	0.97
250	902.10	5.46	4.93	0.102	2.117	1.22
255	900.78	5.32	4.79	0.102	2.127	1.56
260	899.46	5.19	4.67	0.101	2.137	1.83
265	898.13	5.06	4.55	0.100	2.146	2.13
270	896.81	4.94	4.43	0.099	2.156	2.40
275	895.49	4.82	4.32	0.099	2.166	2.67
280	894.17	4.71	4.21	0.098	2.175	2.98
285	892.85	4.60	4.11	0.097	2.185	3.33
290	891.53	4.50	4.01	0.097	2.195	3.72
295	890.21	4.40	3.91	0.096	2.205	4.16
300	888.88	4.30	3.82	0.095	2.214	4.62
305	887.56	4.21	3.74	0.094	2.224	5.19
310	886.24	4.12	3.65	0.094	2.234	5.94
315	884.92	4.04	3.57	0.093	2.244	6.85
320	883.60	3.95	3.49	0.092	2.254	8.68
325	882.28	3.88	3.42	0.091	2.263	11.85

Fluid properties are typical results and should not serve as a sole resource for determining the correct fluid for a particular application. Please consult an Isel representative to ensure that the product is the correct choice for the application. Revised 9/2018 - M

Caldera 7

Silicone Heat Transfer Fluid



Temperature (°C)	Density (kg/m ³)	Kinematic Viscosity (Centistoke)	Dynamic Viscosity (Centipoise)	Thermal Conductivity (W/m-K)	Heat Capacity (kJ/kg-K)	Vapor Pressure (kPa)
330	880.95	3.80	3.35	0.091	2.273	16.52
335	879.63	3.73	3.28	0.090	2.283	22.76
340	878.31	3.65	3.21	0.089	2.293	31.31
345	876.99	3.59	3.15	0.089	2.303	42.69



5266 Highway Avenue
Jacksonville, FL 32254
USA

toll-free: 1-800-503-9533
phone: 904-378-3232
fax: 904-378-9696

email: sales@iselinc.com
web: www.calderafluids.com

Fluid properties are typical results and should not serve as a sole resource for determining the correct fluid for a particular application. Please consult an Isel representative to ensure that the product is the correct choice for the application. Revised 9/2018 - M

All products manufactured in the USA